

REV.	Description	Date
1	add 12P arrangement	2012/1/2
2	upgrade drawing	2014/3/24

Specification of connector

General Characteristics


- Locking system : screw M12
- Termination : solder
- Shell protection : IP68
- Contact resistance : $\leq 10m\Omega$
- Insulation resistance : $\geq 10M\Omega$

Materials

- Socket contact : brass
- Contact plating : gold
- Female insert : PA
- Ring nut : chromium plated
- O-ring : rubber

Specification of cable

Material Jacket	PVC	PUR
-----------------	-----	-----



RoHS

CONTACT ARRANGEMENT FRONT VIEW (FEMALE)	2P	3P	4P	5P	6P	7P	8P	12P
Rated voltage	250V				125V			60V
Rated current	5A				2A			1A



Unicable Co., Ltd. 國陽電業有限公司
 5F., No. 111-33, Sec. 4, San Ho Road, San Chung City, Taiwan, R.O.C.
<http://www.unicable.com.tw> TEL:+886-2-2286-2122 FAX:+886-2-2286-1010

DATE	2016/10/7	PART NO.	UT-D170F3S-XP
DWN	GINA	REV.	2
CHK			
UNIT	MM		

ITEM	Sensor Connector M12
------	----------------------