


REV.	Description	Date
6	arrangement , rate voltage revise	2014/6/13
7	rated voltage, contact resistance, insertion/withdrawal force revise	2016/4/19
8	rated current revise	2018/10/5
9	arrangement revise	2020/11/23



Specification of connector

General Characteristics

Locking system	: screw M24
Shell protection	: IP67
Rated voltage	: 360V, 60V(9BP)
Rated current	: Large pin 35A : Small pin 10A
Contact resistance	: Large pin <5mΩ : Small pin <30mΩ
Insertion force	: <80N
Withdrawal force	: <80N

Materials

Pin contact	: brass
Contact plating	: gold
Male insert	: PA
Ring nut	: brass/chromium plated

Specification of cable

Material Jacket	PVC	PUR
-----------------	-----	-----

RoHS

CONTACT ARRANGEMENT FRONT VIEW (MALE)								
	2AP	8P	9P	10P	3BP	7BP	9AP	9BP



Unicable Co., Ltd. 國陽電業有限公司

5F., No. 111-33, Sec. 4, San Ho Road., San Chung Dist., New Taipei City, Taiwan
<http://www.unicable.com.tw> Tel:+886-2-2286-2122 Fax:+886-2-2286-1010

DATE	2020/11/23	PART NO.	UT-D259M3-XP
DWN	GINA	REV.	9
CHK			
ITEM	High Power M24	UNIT	MM