

REV.	Description	Date
1	add 5, 6PIN arrangement	2012/3/7
2	upgrade drawing	2014/3/21
3	rated voltage revise	2018/10/5

### Specification of connector

#### General Characteristics

Locking system : screw M8

Termination : solder

Shell protection : IP68

Contact resistance :  $\leq 10\text{m}\Omega$

Insulation resistance :  $\geq 10\text{M}\Omega$

#### Materials


Socket contact : brass

Contact plating : gold

Female insert : PA

Ring nut : chromium plated

O-ring : rubber



### Specification of cable

Material Jacket	PVC	PUR

RoHS

CONTACT ARRANGEMENT FRONT VIEW (FEMALE)	3P	4P	5P	6P
Rated voltage	125V		60V	
Rated current	5A		2A	



**Unicable Co., Ltd. 國陽電業有限公司**

5F., No. 111-33, Sec. 4, San Ho Road., San Chung Dist., New Taipei City, Taiwan, R.O.C.  
<http://www.unicable.com.tw> TEL:+886-2-2286-2122 FAX:+886-2-2286-1010

ITEM	Sensor Connector M8	DATE	2018/10/5	PART NO.	UT-P209F3-XP
		DWN	GINA	REV.	3
		CHK			
		UNIT	MM		