


pin no.  
 Part No. : UT-5269-XP-X  
 1-cable OD : 7.5-8.5mm  
 2-cable OD : 8.6-9.5mm  
 3-cable OD : 9.6-10.5mm  
 4-cable OD : 10.6-11.5mm


REV.	Description	Date

Specification of connector

Locking system : Quick Push Lock  
 Termination : solder  
 Shell protection : IP68  
 Contact resistance : <10mΩ  
 Insulation resistance : >10MΩ



Cable preparation



RoHS  
 TOLERANCE ±0.5

6	Nut	PA
5	Seal	TPR
4	Body	PA
3	Coupling ring	PA
2	Terminal	Brass/Gold plated
1	Male insert	PA
Item	Description	Material&Plating

CONTACT ARRANGEMENT FRONT VIEW (MALE)	2P		3P		4P		5P		6P	
Rated voltage	300V			250V			60V			
Rated current	20A			10A			10A			



**Unicable Co., Ltd. 國陽電業有限公司**  
 5F., No. 111-33, Sec. 4, San Ho Road., San Chung Dist., New Taipei City, Taiwan  
<http://www.unicable.com.tw> Tel:+886-2-2286-2122 Fax:+886-2-2286-1010

DATE	2020/9/25	PART NO.	UT-5269-XP-X
DWN	GINA	REV.	0
CHK			
UNIT	MM		

ITEM	Type J(J3): male conn. 2-6P
------	-----------------------------